



## ANNUAL INSPECTION REPORT

Initial/Annual

Report No:

BBB025

Date of inspection:

24 March 2025

Valid until:

23 March 2026

### Unit Details

Name: Game  
Manufacturer: Airquee  
Size and Height: 6.3 x 7.6x 1.2m  
Serial/TAG No: P50776  
Description: Gladiator



Inspector: Peter Grand  
Inspection Co: Grand Affairs Group  
AI0120  
Customer: Bouncy Bouncy Boo  
Place of Inspection: Wolverhampton

Anchorage		Detail	Anchor Points		Detail	Additional Details	
Anchor points	Pass	Contin	Surface Area Sides	N/A	N/A	Anchor Type	Triangle PVC
Anchor Accessories	Pass	16/380	Surface Area Back	N/A	N/A	Number of Anchors	12
Structure						Open Side Fall Off H	0.53m
Seam security	Pass	No Issues	Slides			Outside Wall Height	N/A
Stitching	Pass	4-5mm	Platform Height	N/A	N/A	Inside Wall Height	N/A
Blower Distance	Pass	2.60m	Height walls platform	N/A	N/A	Play Area Square M	N/A
Walls & Towers	Pass	Upright	Height of walls 1st m	N/A	N/A	Maximum User H	Max No Users
Step/Ramp Size	N/A	N/A	Height of walls slope	N/A	N/A		1.0m 2
Grounding	Pass	85kgs	Run out	N/A	N/A		1.2m 2
Sharp Angles	Pass	No Issues	Clamber net	N/A	N/A		1.5m 2
Pressure	Pass	1.19kpa	Slide sheet	N/A	N/A		1.8m 2
Fall Off Height (bed)	Pass	0.53m	Totally Enclosed Structures			<b>Notes:</b> Maximum operating wind speed outdoors - 24mph. - All anchor points to be used outdoors using ground stakes minimum size 16mm x 380mm or equivalent 163kgs per anchor point if setting up on hard surface. - Stakes should not protrude more than 25mm above ground level. - Minimum operating pressure 1kPa. - Mats to be used at entrance/exit when operating on hard surface. - Adult supervision always. - Manufacturers Operation manual must always be followed. - Pressure to be checked and recorded prior to each use. <b>Risk Assessment:</b>	
Trough Depth	Pass	.35/.05m	Exits	N/A	N/A		
Entrapment	Pass	No Issues	Exit Markings	N/A	N/A		
Stability	Fail	podium	Independent Support	N/A	N/A		
Deflation/Evacuation	Pass	10+secs	Emergency Lighting	N/A	N/A		
Air Loss	Pass	No Issues	Deflation of user area	N/A	N/A		
Markings	Pass	Contin	Fan				
Identification	Pass	Contin	Suitability	Pass	Pressure		
Fabric strength	Pass	Manu	Inlet and outlet mesh	Pass	No Issues		
Fire retardancy	Pass	Manu	Cable and plug	Pass	No Issues		
Zips	Pass	2 covered	Impeller	Pass	No Issues		
Thread	Pass	Manu	Return Flap	Pass	No Issues		
Ropes	N/A	N/A	PAT Test	Pass	Own		
Netting	N/A	N/A	Fan Size	1 x 1.5hp			
Windows	N/A	N/A	Manufacturer	Gibbons Fans			

### INITIAL/ANNUAL INSPECTION REPORT

I certify that the equipment identified above was inspected and complied with the safety criteria required using all relevant sections of the European Standard EN 14960, manufacturers/designers/suppliers' information and all other historical information available on the date of inspection.

Result Of Inspection

FAILED

*Peter Grand*

PETER GRAND  
Registered Inspector

### Inspectors Contact Details

Inflatable Testing and Training Service  
58 Station Road Puckeridge Ware SG11 1TF  
Tel: 07940 183600  
Email: office@itats.co.uk

This inspection report is only valid if embossed here by inspection company



## CONTINUATION SHEET



12 around base

The podiums do not support weight over 40kgs and therefore is not useable.



40 kgs



60kgs



80kgs

Many Clients will only allow inflatable equipment on their sites if it is PIPA compliant. The problem is that all inflatables are not currently covered by the scope of the PIPA scheme. Those items not covered by the PIPA scheme include, multi ride beds, surf beds, tumble tracks, bungee runs, pole joust, gladiator joust, inflatable games, inflatable parks and all water-based inflatables. Non-Ride On games\*/Playzones **ARE** included within the PIPA scheme.

\*Non-ride on games - Inflatable games which a person does not have to get onto, into or inside the device to participate. The user can come into contact and interact briefly. They are of a constant air design, and not sealed air units. Examples Include: - Archery & Shooting Ranges - Basketball hoops - Lassos - Bowling Alleys - Dartboards